

新能源汽车用薄膜电容器

Film Capacitor For New Energy Vehicle

YHB



特点与用途

- ◆应用于直流滤波电路中；
- ◆等效串联电阻小，能承受较大的纹波电流；
- ◆能承受高的峰值电流冲击；
- ◆自感小；
- ◆产品温度适用范围广，寿命长；
- ◆采用耐高温聚丙烯安全薄膜设计，自愈性强；
- ◆采用绝缘外壳，导热性树脂灌封，阻燃等级达到 UL94V-0级；
- ◆大功率电力电子设备作滤波或储能用；
- ◆交通工具，如：电动车和混合动力车；
- ◆焊接设备，电梯，电机驱动；
- ◆变速传动（驱动、牵引）。



Features & Applications

- ◆ Applicable to DC filter circuits.
- ◆ Low equivalent series resistance and able to withstand high ripple current.
- ◆ Able to withstand impacting of high-peak current.
- ◆ Low self-inductance.
- ◆ Suit for a wide range of application because of the product's temperature, long service life.
- ◆ High-temperature resistant metallized PP film, excellent self-healing performance.
- ◆ Insulated housing, potted with thermal conductive resin, the flame retardant level reaches UL94V-0.
- ◆ Applicable to high power electronic devices used as filtering or energy storage.
- ◆ Vehicles: eg.:electromobile and hybrid power vehicle.
- ◆ Welding equipment, elevator, motor driving.
- ◆ Variable speed drive (drive and traction).

认证 Certification		
	中国 China	GB/T 17702-2013
	德国 Germany	IEC 61071:2007
AEC-Q200	美国 USA	AEC-Q200 REV D:2010

技术参数 Technical Parameter

气候类别 Climatic category	40/105/56
工作温度 Working temperature	-40°C ~ +105°C
(Under +85°C ~ +105°C, temperature increased by one degree, voltage reduced 1.35U _N) [Θmax(hotspot) ≤ +105°C]	
存储温度 Storage temperature	-40°C ~ +105°C
额定电压 Rated voltage	400Vdc ~ 900Vdc
电容量范围 Range of capacitance	280 μF ~ 1800 μF
电容量允许偏差 Allowable capacitance deviation	±5%(J), ±10%(K)
极间测试电压 Voltage test between terminals	1.5U _N (10s, 25°C ± 5°C)
极壳测试电压 Voltage test between terminals and case	3000Vac
	(60s, 50/60Hz, 25°C ± 5°C)
介质损耗角正切 Dielectric dissipation factor	2 × 10 ⁻⁴
过电压 Over-voltage	1.1U _N (30% of on-load-dur)
	1.15U _N (30min/day)
	1.2U _N (5min/day)
	1.3U _N (1min/day)
	1.5U _N (30ms every time, 1000times)

时间常数 Time constant	≥ 10 000s (25°C ± 5°C, 500V)
等效串联电阻 Equivalent series resistance	0.1 ~ 1.0mΩ (10kHz)
自感 Self inductance	5nH ~ 40nH
最大纹波电流 Maximum ripple current	50A ~ 300A
最大峰值电流 Maximum peak current	2kA ~ 8kA
失效率 Loss of efficiency	50 FIT
最高使用海拔 Maximum application altitude	2000m
最高工作湿度 Maximum working humidity	65°C, 93% RH
最大电极扭矩 Maximum terminal torque	4.5Nm
最大安装扭矩 Maximum installation torque	8.5Nm
灌封材料 Potting material	导热性阻燃树脂 Thermal conductive resin
外壳材料 Material of case	PPS
外形尺寸 Outline dimension	根据用户要求定制 According to customer's requests
预期寿命参考曲线参照 YHK	
Life expectancy reference curve refers to YHK	