

特点与用途

- ◆ 铁芯采用无取向性硅钢片,环氧灌注,性价比高;
- ◆ 整体结构为方形,结构紧凑,外形美观;
- ◆ 噪音小,满足盐雾要求;
- ◆ 连接器结构便于客户安装使用;
- ◆ 主要是作为家电滤波提高功率因素使用.

Features & Applications

- The on-board reactor core of home appliances adopts non-oriented silicon steel sheet, simple processing, cost-effective;
 The overall structure is square, compact structure, beautiful appearance;
 Low noise, and the pin structure is convenient for customers to install and use;
 The connector structure is convenient for customers to install and use
 It is mainly used as a filter for home appliances to improve the power factor.





工作电压 Operating voltage	100VAC-400VAC	工作电流 Operating current	1.3A-5.2A
工作频率 Operating Frequency	50/60Hz	绝缘电阻 Insulation resistance	1.500V DC 绝缘阻值 ≥ 100M Ω
绝缘等级 Insulation class	CLASS B	抗电强调 Electrical strength	铁芯-绕组 1500VAC/50Hz/1mA/3S 无飞狐击穿(工厂测试)



℃订购方式:+86 563 4183767/4186118 区 czy@ngyh.com 了解更多产品信息,敬请登录: ⑧ www.ngyh.com